

Net Power

NPW-UPS System



LINE INTERACTIVE



Tower



1:1 600-2000 VA



USB plug



Plug & Play installation

HIGHLIGHTS

- Automatic Voltage Regulation (AVR)
- Advanced communications
- Automatic battery test

The Net Powerseries is available in 600-2000 VA models with digital technology: when available the load is supplied from the mains power supply, which is amplitude-stabilised by the automatic voltage regulator (AVR) and filtered against overvoltages by EMI filters.

When the mains fails, the load is powered from a pseudo-sine wave inverter, to provide sufficient runtime for computer system shutdown using PowerShield³ software, which can be downloaded free from www.riello-ups.com

Features

- Stabilisation and filtering of the mains power supply using AVR and EMI filters for the suppression of atmospheric disturbances
- Ability to switch on the UPS in the absence

of mains power (Cold Start)

- High reliability with built-in battery test
- Auto restart (when mains power is restored, after discharge of the batteries)
- Supplied with two IEC cables for powering the loads.

Advanced communications

- Advanced multi-platform communications for all operating systems and network environments: PowerShield³ supervision and shutdown software for Windows operating systems 8, 7, Hyper-V, 2012, 2008, and previous versions, Mac OSX, Linux, VMWare ESXi, Citrix XenServer and other Unix operating systems
- Standard USB interface, RS232 on models 1000 - 1500 - 2000.

MODELS	NPW600	NPW800	NPW1000	NPW1500	NPW2000
POWER	600 VA/360 W	800 VA/480 W	1000 VA/600 W	1500 VA/900 W	2000 VA/1200 W
INPUT					
Nominal voltage	220-230-240 Vac				
Input voltage tolerance	230 Vac(±25%)				
Frequency	50/60 Hz with automatic selection				
OUTPUT					
Voltage during mains operation	230 Vac(-8%, +10%)				
Voltage during battery operation	230 Vac(+/- 5%)				
Frequency during battery operation	50 or 60 Hz(+/- 0.5%)				
Battery waveform	Pseudo sinusoidal				
BATTERIES					
Type	VRLAAGM maintenance-free lead based				
Recharge time	6-8 h		2-4 h		
OTHER FEATURES					
Net weight (kg)	4.3	4.9	8	11.1	11.5
Gross weight (kg)	5.6	6.3	10	13.5	14
Dimensions (WxDxH)(mm)	100 x 287 x 142		146 x 350 x 160		146 x 397 x 205
Packaged dimensions (WxDxH) (mm)	140 x 332 x 220		195 x 440 x 250		230 x 480 x 280
Protections	Excessive low battery - overvoltage - short circuit				
Communications	USB		USB + RS232		
Output sockets	4 IEC320 C13 sockets			6 IEC320 C13 sockets	
Standards	EN62040-1-1 and Directive 2006/95/EC; EN62040-2 category C2 and Directive 2004/108 EC				
Certificates	CE				
Operating temperature	0 °C/ +40 °C				
Colour	Black				
Altitude and relative humidity	6000 m max altitude, <95% non-condensing				
Standard equipment	2 cables for powering loads; user manual				

AVAILABLE OPTIONS

SOFTWARE

PowerShield³

ACCESSORIES

NETMAN204 + box
(only NPW1000-2000)

MULTICOM302 + box
(only NPW1000-2000)

DETAILS

